



## Samojistící šestihranný šroub s nákrůžkem DIN ≈6921 Ocel Pravý Bez PU 100 M12X35

|                |                   |
|----------------|-------------------|
| Číslo produktu | 01050.120.035     |
| Značka         | -                 |
| UBB            | 950351125071      |
| UNSPSC         | 31161620          |
| EAN            | 8715492019219     |
| BAL. od 100    | Pouze celé balení |

### Technické parametry

|                         |                       |
|-------------------------|-----------------------|
| Průměr (d-D)            | M12                   |
| Délka (L) (mm)          | 35                    |
| Třída                   | 100                   |
| Typ drážky              | S vnějším šestihranem |
| Tvar hlavy              | Šestihranná hlava     |
| Materiál (dlouhý název) | Ocel                  |
| Směr závitů             | Pravý                 |
| Povrchová úprava        | Bez PU                |
| Závit                   | Metrický závit        |

**Poznámky**

Specific features of self-locking hexagon bolts with toothed flange: The resilient toothed flange ensures excellent self-locking properties. The smooth bearing surface in the center of the flange guarantees a high clamping force, with minimal relaxation. Washers and/or locking elements are not necessary

### Standardy

DIN ≈6921

and are even not advisable. Self-locking hexagon bolts with toothed flange are designated with property class 90 or 100 with a minimum tensile strength Rm of 900/1000 MPa, they are case hardened and therefore cannot be classified as property class 9.8/10.9.

#### Info

Warning: electroplating of these products may cause hydrogen embrittlement.

### Technická specifikace

|                |      |
|----------------|------|
| d <sub>c</sub> | 24   |
| P              | 1.75 |
| k              | 8.7  |
| s              | 17   |

### Technický náčrt

