



**Šroub s půlkulatou hlavou,
čtvercovým krkem a
šestihrannou maticí,
zvětšený závit DIN 603/555
Ocel Žárový zinek ≥ 4.6
M10X80**

Číslo produktu	08420.100.080
Značka	-
UBB	950351639972
UNSPSC	31161612
EAN	8715492561077
BAL. od 100	Pouze celé balení

Technické parametry

Průměr (d-D)	M10
Délka (L) (mm)	80
Třída	≥ 4.6
Materiál (dlouhý název)	Ocel
Směr závitu	Pravý
Povrchová úprava	Žárový zinek
Závit	Metrický závit

Standardy

DIN	603/555
BS	4933/-
ISO	8677/-
ASME	B18.5.2.3M/-
NF	- / E25-402
NEN	303/697

Info

Oversized hot dip galvanized bolts and screws are manufactured with standard thread tolerance class 6g before coating. After galvanizing they will therefore NOT fit into standard nuts or threaded holes with thread tolerance class 6H. Suitable nuts have been tapped with thread tolerance class 6AZ (oversized).

Technická specifikace

FARORY

d_k (max.)	24.65
--------------	-------

b (min.): $L \leq 125\text{mm}$	26
-----------------------------------	----

f_n (max.)	6.6
--------------	-----

s	17
-----	----

P	1.50
-----	------

V_n (max.)	10.58
--------------	-------

m	8
-----	---

b (min.): $L > 200\text{mm}$	45
--------------------------------	----

k (max.)	5.38
------------	------

b (min.): $125\text{mm} < L \leq 200\text{mm}$	32
---	----

Technický náčrt

