



**Šroub s půlkulatou hlavou,
čtvercovým krkem a
šestihrannou maticí,
zvětšený závit DIN 603/555
Ocel Žárový zinek ≥ 4.6
M12X260**

Číslo produktu	08420.120.260
Značka	-
UBB	950351642844
UNSPSC	31161612
EAN	8715492561367
BAL. od 25	Pouze celé balení

Technické parametry

Průměr (d-D)	M12
Délka (L) (mm)	260
Třída	≥ 4.6
Materiál (dlouhý název)	Ocel
Směr závitu	Pravý
Povrchová úprava	Žárový zinek
Závit	Metrický závit

Info

Oversized hot dip galvanized bolts and screws are manufactured with standard thread tolerance class 6g before coating. After galvanizing they will therefore NOT fit into standard nuts or threaded holes with thread tolerance class 6H. Suitable nuts have been tapped with thread tolerance class 6AZ (oversized).

Standardy

ASME	B18.5.2.3M/-
DIN	603/555
BS	4933/-
NF	- / E25-402
NEN	303/697
ISO	8677/-

Technická specifikace

FARORY

Vn (max.)	12.7
m	10
fn (max.)	8.75
b (min.): $L \leq 125\text{mm}$	30
k (max.)	6.95
s	19
b (min.): $125\text{mm} < L \leq 200\text{mm}$	36
b (min.): $L > 200\text{mm}$	49
d_k (max.)	30.65
P	1.75

Technický náčrt

