



## Svorník se 2 šestihrannými maticemi ASME B16.5/ B18.2.2 Nerezocel ASTM A193 - ASTM A194 Pravý Gr.B8 Cl.2 - Gr.8 3/4X85 (3.3/8)

|                |                   |
|----------------|-------------------|
| Číslo produktu | 22529.191.085     |
| Značka         | -                 |
| UBB            | 500578424730      |
| UNSPSC         | 31161619          |
| EAN            | 8715494359177     |
| BAL. od 1      | Pouze celé balení |

### Technické parametry

|                |       |
|----------------|-------|
| Průměr         | 3/4   |
| Délka (L) (mm) | 85    |
| Délka (mm)     | 3.3/8 |

#### Info

Tolerances of the total length of the studbolts according to ASME B16.5 Table C-3 L is the nominal length of the studbolt, measured from the first to the last full thread and thus excluding the chamfered ends.

|                         |                         |
|-------------------------|-------------------------|
| Třída                   | Gr.B8 Cl.2 - Gr.8       |
| Materiál (dlouhý název) | Nerezocel               |
| Technický materiál      | ASTM A193 - ASTM A194   |
| Směr závitu             | Pravý                   |
| Závit                   | Unified National Coarse |

#### Poznámky

Grade 4 nuts are no longer in ASTM A194/A194M and

### Standardy

|      |                 |
|------|-----------------|
| ASTM | A193/A194       |
| ASME | B16.5 / B18.2.2 |
| BS   | 4882            |

will be phased  
out gradually.  
It is advised to  
use Grade 7 nuts  
instead.

## Technická specifikace

|                 |       |
|-----------------|-------|
| B               | 1.1/4 |
| Závitů na palec | 10    |
| M               | 18.7  |

## Technický náčrt

