



**Svorník se 2 šestihrannými  
maticemi ASME B16.5/  
B18.2.2 Nerezocel ASTM  
A193 - ASTM A194 Pravý  
Gr.B8M Cl.2 - Gr.8M  
1.1/4X145 (5.3/4)**

|                |                   |
|----------------|-------------------|
| Číslo produktu | 22539.317.146     |
| Značka         | -                 |
| UBB            | 500578143082      |
| UNSPSC         | 31161619          |
| EAN            | 8715494326612     |
| BAL. od 1      | Pouze celé balení |

**Technické parametry**

|                |       |
|----------------|-------|
| Průměr         | 1.1/4 |
| Délka (L) (mm) | 145   |
| Délka (mm)     | 5.3/4 |

**Info**

Tolerances of the total length of the studbolts according to ASME B16.5 Table C-3 L is the nominal length of the studbolt, measured from the first to the last full thread and thus excluding the chamfered ends.

|                         |                                                                  |
|-------------------------|------------------------------------------------------------------|
| Třída                   | Gr.B8M Cl.2 - Gr.8M                                              |
| Materiál (dlouhý název) | Nerezocel                                                        |
| Technický materiál      | ASTM A193 - ASTM A194                                            |
| Směr závitů             | Pravý                                                            |
| Závit                   | 8 Unified National                                               |
| Poznámky                | Grade 4 nuts are no longer in ASTM A194/A194M and will be phased |

**Standardy**

|      |                 |
|------|-----------------|
| ASME | B16.5 / B18.2.2 |
| ASTM | A193/A194       |
| BS   | 4882            |

out gradually.  
 It is advised to  
 use Grade 7 nuts  
 instead.

## Technická specifikace

|                 |       |
|-----------------|-------|
| Závitů na palec | 8     |
| M               | 31    |
| B               | 2.IN. |

## Technický náčrt

