



Prohnutá pružná pojistná podložka DIN ≈128 A Nerezocel A2 M8

Číslo produktu	51520.080.001
Značka	-
UBB	950357313309
UNSPSC	31161811
EAN	8715492294289
BAL. od 200	Pouze celé balení

Technické parametry

Pro jmenovitý rozměr M8	
Materiál (dlouhý název)	Nerezocel
Technický materiál	A2

Standardy

DIN	≈128 A
NEN	≈1570

Info

The measurements deviate slightly from DIN 128 A, these spring lock washers have a deviating "reinforced" thickness resulting in considerably improved spring characteristics. Curved spring lock washers acc. to DIN 128 A are improved compared to spring lock washers acc. to DIN 127 A and due to the curved form have moreover the advantages: do not damage surfaces of the construction, nut or bolt; also to use with left hand thread; do not disform during tightening and disassembly, thus re-useable; do not

tangle, so suitable for automatic feeding. Use under dynamic load is not allowed. For locking under dynamic load is referred to NORD-LOCK vibration proof washers. The austenetic steel type is at the manufacturer's discretion, and can vary from the steel types stated in DIN 267-11.

Technická specifikace

s	1.6
d ₂ (max.)	14.8
d ₁ (min.)	8.1

Technický nákres

