



Prohnutá pružná pojistná podložka DIN ≈128 A Nerezocel A2 M18

Číslo produktu	51520.180.001
Značka	-
UBB	950357410576
UNSPSC	31161811
EAN	8715492294333
BAL. od 100	Pouze celé balení

Technické parametry

Pro jmenovitý rozměr M18

Materiál (dlouhý
název) Nerezocel

Technický materiál A2

Info

The measurements deviate slightly from DIN 128 A, these spring lock washers have a deviating "reinforced" thickness resulting in considerably improved spring characteristics. Curved spring lock washers acc. to DIN 128 A are improved compared to spring lock washers acc. to DIN 127 A and due to the curved form have moreover the advantages: do not damage surfaces of the construction, nut or bolt; also to use with left hand thread; do not disform during tightening and disassembly, thus re-useable; do not

Standardy

NEN ≈1570

DIN ≈128 A

tangle, so suitable for automatic feeding. Use under dynamic load is not allowed. For locking under dynamic load is referred to NORD-LOCK vibration proof washers. The austenetic steel type is at the manufacturer's discretion, and can vary from the steel types stated in DIN 267-11.

Technická specifikace

s	2.8
d ₂ (max.)	29.4
d ₁ (min.)	18.2

Technický nákres

