



## Prohnutá pružná pojistná podložka DIN ≈128 A Nerezocel A2 M24

Číslo produktu	51520.240.001
Značka	-
UBB	950357410733
UNSPSC	31161811
EAN	8715492294364
BAL. od 50	Pouze celé balení

### Technické parametry

Pro jmenovitý rozměr	M24
Materiál (dlouhý název)	Nerezocel
Technický materiál	A2

#### Info

The measurements deviate slightly from DIN 128 A, these spring lock washers have a deviating "reinforced" thickness resulting in considerably improved spring characteristics. Curved spring lock washers acc. to DIN 128 A are improved compared to spring lock washers acc. to DIN 127 A and due to the curved form have moreover the advantages: do not damage surfaces of the construction, nut or bolt; also to use with left hand thread; do not disform during tightening and disassembly, thus re-useable; do not

### Standardy

DIN	≈128 A
NEN	≈1570

tangle, so suitable for automatic feeding. Use under dynamic load is not allowed. For locking under dynamic load is referred to NORD-LOCK vibration proof washers. The austenetic steel type is at the manufacturer's discretion, and can vary from the steel types stated in DIN 267-11.

## Technická specifikace

$d_1$ (min.)	24.5
s	4
$d_2$ (max.)	40

## Technický nákres

