



Prohnutá pružná pojistná podložka DIN ≈128 A Nerezocel A2 M30

Číslo produktu	51520.300.001
Značka	-
UBB	950357410998
UNSPSC	31161811
EAN	8715492294371
BAL. od 25	Pouze celé balení

Technické parametry

Pro jmenovitý rozměr	M30
Materiál (dlouhý název)	Nerezocel
Technický materiál	A2

Info

The measurements deviate slightly from DIN 128 A, these spring lock washers have a deviating "reinforced" thickness resulting in considerably improved spring characteristics. Curved spring lock washers acc. to DIN 128 A are improved compared to spring lock washers acc. to DIN 127 A and due to the curved form have moreover the advantages: do not damage surfaces of the construction, nut or bolt; also to use with left hand thread; do not disform during tightening and disassembly, thus re-useable; do not

Standardy

DIN	≈128 A
NEN	≈1570

tangle, so suitable for automatic feeding. Use under dynamic load is not allowed. For locking under dynamic load is referred to NORD-LOCK vibration proof washers. The austenetic steel type is at the manufacturer's discretion, and can vary from the steel types stated in DIN 267-11.

Technická specifikace

d_1 (min.)	30.5
d_2 (max.)	48.2
s	6

Technický nákres

