



Prohnutá pružná pojistná podložka DIN ≈128 A Nerezocel A2 M36

| | |
|----------------|-------------------|
| Číslo produktu | 51520.360.001 |
| Značka | - |
| UBB | 950357411152 |
| UNSPSC | 31161811 |
| EAN | 8715492294388 |
| BAL. od 25 | Pouze celé balení |

Technické parametry

Pro jmenovitý rozměr M36

Materiál (dlouhý
název) Nerezocel

Technický materiál A2

Info

The measurements deviate slightly from DIN 128 A, these spring lock washers have a deviating "reinforced" thickness resulting in considerably improved spring characteristics. Curved spring lock washers acc. to DIN 128 A are improved compared to spring lock washers acc. to DIN 127 A and due to the curved form have moreover the advantages: do not damage surfaces of the construction, nut or bolt; also to use with left hand thread; do not disform during tightening and disassembly, thus re-useable; do not

Standardy

DIN ≈128 A

NEN ≈1570

tangle, so suitable for automatic feeding. Use under dynamic load is not allowed. For locking under dynamic load is referred to NORD-LOCK vibration proof washers. The austenetic steel type is at the manufacturer's discretion, and can vary from the steel types stated in DIN 267-11.

Technická specifikace

| | |
|-----------------------|------|
| s | 6 |
| d ₂ (max.) | 58.2 |
| d ₁ (min.) | 36.5 |

Technický nákres

