| Product<br>code                | BPPB 1603 2100   |                | C. B.C.  |
|--------------------------------|--|----------------|--|
|                                | BPPB 1603 2100   |                |  |
| Long                           | Swivel fork of deep drawn zinc-coated steel. Swivel  |                |  |
| description                    | n bearing with double ball race and sealring with brake.<br>Hub width 60 mm. Top Plate 140x110 mm. Bolt hole |                |  |
|                                | spacing 105x80 mm. Polyamide wheel   |                |  |
|                                | tyre, 70° Shore A with roller bearing. Bo  | re diameter 20 |  |
|                                | mm. Diameter 160 mm. Load capacity 2<br>Temperature Range -20 / +80 °C.                                      | 20 kg.         | Aller and a second   |
|                                | Colson Direct Range. Page 40-41.   |                |  |
| Overall                        |  |                |  |
| height                         | 195 mm   |                |  |
|                                | $\bigcirc$   |                |  |
| Weight                         | 2.9 kg   |                |  |
|                                |  |                |  |
| Load<br>capacity               | 220 kg   |                |  |
| Catalogue                      | Colson Direct Range  |                |  |
| Series Light Industrial Series |  |                |  |
| Page                           | 40-41  |                |  |
| U                              |  |                |  |
| Wheel                          | Polyamide wheel with blue rubber   | Fork           | Swivel fork of deep drawn zinc-coated                                |
| description                    | tyre, 70° Shore A with roller<br>bearing   | Description    | steel. Swivel bearing with double ball race and sealring with brake. |
|                                | bearing  |                |  |
| Wheel                          | WPPB 1603 2000   | Top Plate      | 140x110 mm   |
|                                |  |                |  |
| Diameter                       | ( <b>(</b> ) 160 mm  | Bolt hole      | 105x80 mm  |
|                                |  | spacing        | <u>±</u> 0   |
| Bushing typ                    | HAX 201361D  | Fixing bolt    | <b>★</b> • • • • • • • • • • • • • • • • • • •                       |
| Busining typ                   |  | diameter       |  |
| _                              | <u>A</u>   |                |  |
| Bore diamet                    | ter 20 mm  | Offset         | 60 mm  |
|                                | л.<br>Л  |                |  |
| Hub width                      | 60 mm  |                |  |
|                                |  |                |  |
| Thread widt                    | <b>h H</b> 45 mm   |                |  |
|                                | ->\\<br>   |                |  |
|                                |  |                |  |
| Bearingtype                    | with roller bearin   |                |  |