

Approved for the storage of flammable liquids at the workplace as per DIN EN 14470-1 (type 90) and TRGS 510, annex 1, toxic and very toxic substances, acids and alkalis. Ideal combination for storage of various hazardous substances in a very small space.



Safety cabinet (type 90) for flammable liquids as per DIN EN 14470-1

- Whole construction tested and approved by an authorized materials testing Institute as per DIN EN 14470-1 (type 90) with a fire resistance >90 minutes
- GS-approved safety (GS-sign)
- Insulation according to DIN 4102
- Outer body made from powder-coated sheet steel in RAL 7035 light grey
- Inner body made from HPL-coated sheets in RAL 7035 light grey
- Stainless steel base plate Niro Rhombus
- Shelf height-adjustable at intervals of 64 mm
- DN 80 ventilation connection for exhaust air extraction on cabinet roof
- Operation complies with TRGS 510 (approved even without exhaust air connection!)
- Ground connection in accordance with TRBS 2153 (avoidance of sources of ignition)
- Markings according to DIN EN 14470-1 / TRGS 510 / ISO 3864 / ASR A1.3
- Leveling feets for installing cabinet horizontally

4

Doors with cylinder lock



Type 90 / 1200 KL1, Article no. B80-2627-A

With inner fittings:

1 Safety cabinet (type 90)

- 1 x base sump tray (sump capacity 22 liters) as per WHG Ü-sign according to StawaR
- 1 x perforated base tray cover as 1st storing level
- 2 x shelf
- Automatic thermal closing mechanism if fire occurs
- Door after temperature increase to ≤50°C and
- Inlet and outlet channels after temperature increase to 70°C (±10°C)
- door hold-open device

2 Storage cabinet for acids and alkalis

- 2 x 2 or 2 x 3 pull-out tray-shaped shelves, made from white PE
- Model GL with acrylic glass doors
- **3** Poison compartment with acrylic glass door
 - Dividing shelf
- 4 Cover panel made from HPL-coated sheets in RAL 7035 light grey

	Type 90 / 1200 KL1	Type 90 / 1200 KL2	Type 90 / 1200 KL3 GL
	1195 x 600 x 1935	1195 x 600 x 1935	1195 x 600 x 1935
	4	4	4
Pull-out shelves	4	6	6
Usable inner height (mm)	4 x 420	4 x 275 / 2 x 248	4 x 275 / 2 x 248
	325	335	340
Material inner fittings			
sheet steel	B80-2820-A	B80-2821-A	B80-2822-A
sheet steel	B80-2627-A	B80-2628-A	B80-2629-A
	Usable inner height (mm) Material inner fittings sheet steel	1195 x 600 x 1935 4 Pull-out shelves 4 Usable inner height (mm) 4 x 420 325 Material inner fittings sheet steel B80-2820-A	1195 x 600 x 1935 1195 x 600 x 1935 4 4 Pull-out shelves 4 6 4 x 420 Usable inner height (mm) 4 x 420 325 335 Material inner fittings 5heet steel B80-2820-A B80-2821-A

plus cover panel: height 110 mm

2 1

4





Article no. B80-2822-A